

GENERAL INFORMATION

UNITED LIGHTING STANDARDS, INC.

23171 Groesbeck Hwy. • Warren, MI 48089
Tel: 586/774-5650 FAX: 586/774-5706

Standard Accessories

- 1) Anchor Bolts & Template
- 2) Base Plate Cover
- 3) Handhole Cover
- 4) Grounding Provision
- 5) Tenon - specify 2.375", 3", or 4" O.D.
- 6) Direct Drill Mounting - specify luminaire type and configuration
(see page 6)
- 7) Pole Cap - for poles with direct drill mounting
- 8) Polyester Powder Coat Finish - specify color
 - standard colors: dark bronze (DB)
 - contact agency or factory for custom colors including silver (SL), grey (GR), white (WHT) or black (BLK)

Available Options

- | | |
|------------------------------|---|
| • Duplex Receptacle | DR -- A weatherproof recessed receptacle for 125 volt 15-amp A.C. current. |
| • Welded Nipple | WN -- A threaded pipe nipple with wire hole - specify size and location. |
| • Welded Coupling | WC -- A threaded pipe coupling with wire hole - specify size and location. |
| • Galvanizing | GV -- Hot dipped galvanizing - insert GV under pole finish. |
| • Lowering Winch | LW -- Recommended for use with hinged poles. |
| • Vibration Dampener | VD -- Recommended for aluminum poles 30' and higher. |
| • Welded Mounting Bracket | WB -- 2.375" O.D bent slipfit pipe bracket welded on pole - specify location. |
| • GFI Receptacle | GFI -- Weatherproof 15-20 amp. 110-125v Ground Fault Interrupter. |
| • Transformer Bases | -- FHWA approved breakaway transformer bases - contact factory for details. |
| • Direct Burial Modification | -- Specify mounting height. |

Contact agent or factory for prices and custom options not listed in catalog.